

Stigeledningsklemme 1x35+2x16 mm²

Material	Polycarbonat.
Temp. range min	-5 °C
Temp. range max	85 °C
Temperatures during install.	-5 °C - 60 °C
Protection class	IP20
Glow wire test	750 °C
Voltage	450 V
Size of umbraco	3 mm + 6 mm
Tightening torque:	4 Nm
Ø cable diameter min	1x35+2x16 mm ²
Ø cable diameter max	1x35+2x16 mm ²
External dimensions LxWxH	43 x 37 x 43mm
Tariff number	85472000

Application:

Unique compact branching terminal for optimal preservation of space up to 30 to 40% of the width of the old SKhouses. Can be installed in conduits and junction boxes - Combi 607 etc., which requires high quality and standard. This branching terminal is an ideal solution when it is vital to save space. Ideal for shunt for one or more supplies.

Colour:

Transparent protective cover - so you can see the connections.

Safety:

Installation friendly. Possibility of anchoring the terminal, so both hands are free to connect the cable. Can be open when you mount it.

Mounting:

Use flexible conductors recommended to use grommets. This also applies to the use of category 5 cable. Category 5 cable **can't** be used as a **UNBREADED** cable in the terminal. **Can't** be used with aluminum cable.



EL-number	Type	LxBxH	Terminal mm ²	Colour	Packing
1321102204	ACEL120501	43x37x43	1x35+2x16	Transparent	25