



Certificate of constancy of performance

0402 - CPR - SC0079-16

In compliance with *Regulation 305/2011/EU of the European Parliament and of the Council of 9 March 2011* (the Construction Products Regulation or CPR), this certificate applies to the construction product

Hose reels with semi-rigid hose
for use in fixed firefighting systems,
as specified in appendix to this certificate.

Product name: Safeti® by Venti

placed on the market under the name or trademark of

Venti AS
Banevænget 3
DK-8362 Hørning
Denmark

and produced in the manufacturing plant

same as above

This certificate attests that all provisions concerning the assessment and verification
of constancy of performance described in annex ZA of the standard

EN 671-1:2012

under system 1 for the performances set out in this certificate are applied and that the factory
production control conducted by the manufacturer is assessed to ensure the

constancy of performance of the construction product.

This certificate was first issued on 2016-05-24 and will remain valid as long as neither the harmonised
standard, the construction product, the AVCP methods nor the manufacturing conditions in the plant
are modified significantly, unless suspended or withdrawn by the notified product certification body.

2016-05-24

SP Technical Research Institute of Sweden
Certification, Notified Body No. 0402

Lennart Aronsson
Product Certification Manager

Martin Tillander
Certification officer

Certificate of constancy of performance

0402 - CPR - SC0079-16 appendix

Hose reels with semi-rigid hose, *Safeti® by Venti*

Intended for fixed installations to provide the occupants of a building
the means to control and extinguish a fire nearby.

Specifications

Hose reel designation and description	Hose (supplier)	Hose ø (mm)	Max. hose length (m)	Nozzle (supplier)	Nozzle ø (mm)	Cabinet types (type)
399551266, red painted galvanized steel, manual valve. Conical spray nozzle.	Parsch	19	25	AWG	7	2, 2l, 2ig, 2s, 3, 4, 5, 6, 7, 8
399551266, red painted galvanized steel, manual valve. Conical spray nozzle.	Parsch	19	30	AWG	7	2, 2l, 2ig, 3, 4, 5, 6, 7, 8
399551276, red painted stainless steel, manual valve. Conical spray nozzle.	Parsch	19	25	AWG	7	2, 2l, 2ig, 3, 4, 5, 6, 7, 8
399551326, red painted stainless steel, manual valve. Conical spray nozzle.	Parsch	19	30	AWG	7	2, 2l, 2ig, 3, 4, 5, 6, 7, 8
399551268, red painted galvanized steel, manual valve. Conical spray nozzle.	Parsch	25	25	AWG	10 or 8	2, 2l, 2ig, 3, 4, 5, 6, 7, 8
399551318, red painted galvanized steel, manual valve. Conical spray nozzle.	Parsch	25	30	AWG	10 or 8	2, 2l, 2ig, 3, 4, 5, 6, 7, 8
399551278, red painted galvanized steel, manual valve. Conical spray nozzle.	Parsch	25	25	AWG	10 or 8	2, 2l, 2ig, 3, 4, 5, 6, 7, 8
399551328, red painted stainless steel, manual valve. Conical spray nozzle.	Parsch	25	30	AWG	10 or 8	2, 2l, 2ig, 3, 4, 5, 6, 7, 8
399552266, red painted galvanized steel, automatic valve. Conical spray nozzle.	Parsch	19	25	AWG	7	2, 2l, 2ig, 2s, 3, 4, 5, 6, 7, 8
399552316, red painted galvanized steel, automatic valve. Conical spray nozzle.	Parsch	19	30	AWG	7	2, 2l, 2ig, 3, 4, 5, 6, 7, 8
399552276, red painted stainless steel, manual valve. Conical spray nozzle.	Parsch	19	25	AWG	7	2, 2l, 2ig, 3, 4, 5, 6, 7, 8

Table continues on the next page.



Certificate of constancy of performance

0402 - CPR - SC0079-16 appendix

Hose reel designation and description	Hose (supplier)	Hose ø (mm)	Max. hose length (m)	Nozzle (supplier)	Nozzle ø (mm)	Cabinet types (type)
399552326, red painted stainless steel, manual valve. Conical spray nozzle.	Parsch	19	30	AWG	7	2, 2l, 2ig, 3, 4, 5, 6, 7, 8
399552268, red painted galvanized steel, automatic valve. Conical spray nozzle.	Parsch	25	25	AWG	10 or 8	2, 2l, 2ig, 3, 4, 5, 6, 7, 8
399552318, red painted galvanized steel, automatic valve. Conical spray nozzle.	Parsch	25	30	AWG	10 or 8	2, 2l, 2ig, 3, 4, 5, 6, 7, 8
399552278, red painted stainless steel, manual valve. Conical spray nozzle.	Parsch	25	25	AWG	10 or 8	2, 2l, 2ig, 3, 4, 5, 6, 7, 8
399552328, red painted stainless steel, manual valve. Conical spray nozzle.	Parsch	25	30	AWG	10 or 8	2, 2l, 2ig, 3, 4, 5, 6, 7, 8
BP11925, red painted galvanized steel, automatic valve. Conical spray nozzle.	Svebab	19	25	TA	7	2, 2l, 2ig, 2s, 3, 4, 5, 6, 7, 8
BP11930, red painted galvanized steel, automatic valve. Conical spray nozzle.	Svebab	19	30	TA	7	2, 2l, 2ig, 3, 4, 5, 6, 7, 8
BP11925SS, red painted acidproof steel, automatic valve. Conical spray nozzle.	Svebab	19	25	TA	7	2, 2l, 2ig, 3, 4, 5, 6, 7, 8
BP11930SS, red painted acidproof steel, automatic valve. Conical spray nozzle.	Svebab	19	30	TA	7	2, 2l, 2ig, 3, 4, 5, 6, 7, 8
BP12525, red painted galvanized steel, automatic valve. Conical spray nozzle.	Svebab	25	25	TA	10 or 8	2, 2l, 2ig, 3, 4, 5, 6, 7, 8
BP12530, red painted galvanized steel, automatic valve. Conical spray nozzle.	Svebab	25	30	TA	10 or 8	2, 2l, 2ig, 3, 4, 5, 6, 7, 8
BP12525SS, red painted acidproof steel, automatic valve. Conical spray nozzle.	Svebab	25	25	TA	10 or 8	2, 2l, 2ig, 3, 4, 5, 6, 7, 8
BP12530SS, red painted acidproof steel, automatic valve. Conical spray nozzle.	Svebab	25	30	TA	10 or 8	2, 2l, 2ig, 3, 4, 5, 6, 7, 8

Table continues on the next page.



Certificate of constancy of performance

0402 - CPR - SC0079-16 appendix

Hose reel designation and description	Hose (supplier)	Hose ϕ (mm)	Max. hose length (m)	Nozzle (supplier)	Nozzle ϕ (mm)	Cabinet types (type)
BP11925A, red painted galvanized steel, automatic valve. Conical spray nozzle.	Svebab	19	25	TA	7	2, 2l, 2ig, 2s, 3, 4, 5, 6, 7, 8
BP11930A, red painted galvanized steel, automatic valve. Conical spray nozzle.	Svebab	19	30	TA	7	2, 2l, 2ig, 3, 4, 5, 6, 7, 8
BP11925SSA, red painted acidproof steel, automatic valve. Conical spray nozzle.	Svebab	19	25	TA	7	2, 2l, 2ig, 3, 4, 5, 6, 7, 8
BP11930SSA, red painted acidproof steel, automatic valve. Conical spray nozzle.	Svebab	19	30	TA	7	2, 2l, 2ig, 3, 4, 5, 6, 7, 8
BP12525A, red painted galvanized steel, automatic valve. Conical spray nozzle.	Svebab	25	25	TA	10 or 8	2, 2l, 2ig, 3, 4, 5, 6, 7, 8
BP12530A, red painted galvanized steel, automatic valve. Conical spray nozzle.	Svebab	25	30	TA	10 or 8	2, 2l, 2ig, 3, 4, 5, 6, 7, 8
BP12525SSA, red painted acidproof steel, automatic valve. Conical spray nozzle.	Svebab	25	25	TA	10 or 8	2, 2l, 2ig, 3, 4, 5, 6, 7, 8
BP12530SSA, red painted acidproof steel, automatic valve. Conical spray nozzle.	Svebab	25	30	TA	10 or 8	2, 2l, 2ig, 3, 4, 5, 6, 7, 8

Cabinet designation	Description
Type 2	Wall mounted house, with axial water supply and swing arm.
Type 2l	Integrated in wall, with axial water supply and swing arm.
Type 2ig	Integrated in wall, with axial water supply and swing arm.
Type 2s	Wall mounted house, with axial water supply and swing arm.
Type 3	Wall mounted house, with axial water supply and swing arm.
Type 4	Wall mounted house, with axial water supply and swing arm.
Type 5	Wall mounted house, with axial water supply and swing arm.
Type 6	Wall mounted house, with axial water supply and swing arm.
Type 7	Wall mounted house, with axial water supply and swing arm.
Type 8	Wall mounted house, with axial water supply and swing arm.



SP Technical Research Institute of Sweden

Box 857, SE-501 15 Borås, Sweden

Phone: +46 10-516 50 00

E-mail, internet: info@sp.se, www.sp.se

6P01435

Swedish Notified Bodies are appointed by Swedac under the terms of Swedish legislation. This certificate may not be reproduced other than in full. The certificate including appendix consists of 4 pages, where this is page 4. This is issue 1.