



Type..... 57908 101 111
Designation Wireless Power Bank

LED indication



Chemical system Lithium-Polymer
Cell configuration 3x Li-Polymer Pouch cell (5000 mAh), 55.5 Wh

Indications for IN

Power Level	LED Status (LED 1 2 3 4)
100%	● ● ● ●
75%-99%	● ● ● ■
50%-75%	● ● ■ ○
25%-50%	● ■ ○ ○
0-25%	■ ○ ○ ○

Cell size 124 mm x 70 mm
Cell voltage 3.7 V
Total cell capacity 15,000 mAh
Rated capacity 8,880 mAh @ 5V 2A

Blue LED #4: Quickcharge (QC/PD input/output)

Indications for OUT

Power Level	LED Status (LED #1 #2 #3 #4)
75-100%	● ● ● ●
50-75%	● ● ● ○
25-50%	● ● ○ ○
10-25%	● ○ ○ ○
0-10%	■ ○ ○ ○

Input..... 18 W max.
USB Type-C port 5V 3.0A | 9V 2.0A | 12V 1.5A

Blue LED #2: Wireless Charging

Blue LED #4: Quickcharge (QC/PD input/output)

Output..... 20 W max.
USB Type-A port..... 5V 2.4A | 9V 2.0A | 12V 1.5A
USB Type-C port 5V 3.0A | 9V 2.2A | 12V 1.67A
Wireless (Qi) 5W 7.5W 10W

No publication or circulation of data to third parties without consent of VARTA Consumer Batteries

Power IN

Primary..... 5V DC 2.4A

Secondary..... 3.6V DC

Power OUT

Primary..... 3.6V DC

Secondary..... 5V DC 2.4A

Ambient Temperature

Charging..... 0°C - 50°C

Discharging -10°C - 55°C

Storage..... -10°C - 60°C

Cut off criteria.....Stop discharging
when Li-Ion voltage
< 2.8VShort circuit
protection

Overload protection

NTC temperature
protection**Housing**

Material..... Plastic

Upper casing colour White

Lower casing colour Cool grey

Dimensions.....

Length 158.5 ±1 mm

Width 78.5 ±1 mm

Height 19 ±1 mm

Weight 341 ±3 g