

Product Environmental Profile

CRL 20M HO5VVF 3G1.5 IP20 CONTOUR



Schneider
Electric




General information

Representative product	CRL 20M HO5VVF 3G1.5 IP20 CONTOUR - IMT33142
Description of the product	It's a cable reel for enwinding cables and energy transmission.
Functional unit	To transmit energy expressed for 1A over a distance of 1 km during 30 years and a 70% use rate, in accordance with the relevant standards.



Constituent materials

Reference product mass	5132 g including the product, its packaging and additional elements and accessories
------------------------	---



Plastics	14.3%
Metals	34.9%
Others	50.8%



Substance assessment

Products of this range are designed in conformity with the requirements of the RoHS directive (European Directive 2011/65/EU of 8 June 2011) and do not contain, or only contain in the authorised proportions, lead, mercury, cadmium, hexavalent chromium or flame retardants (polybrominated biphenyls - PBB, polybrominated diphenyl ethers - PBDE) as mentioned in the Directive

As the products of the range are designed in accordance with the RoHS Directive (European Directive 2002/95/EC of 27 January 2003), they can be incorporated without any restriction in an assembly or an installation subject to this Directive.

Details of ROHS and REACH substances information are available on the Schneider-Electric Green Premium website

<http://www2.schneider-electric.com/sites/corporate/en/products-services/green-premium/green-premium.page>



Additional environmental information

The CRL 20M HO5VVF 3G1.5 IP20 CONTOUR presents the following relevant environmental aspects


Manufacturing	Manufactured at a Schneider Electric production site ISO14001 certified
Distribution	Weight and volume of the packaging optimized, based on the European Union's packaging directive Packaging weight is 712 g, consisting of cardboard(99.9%), paper(0.1%)
Installation	Reference IMT33142 does not require any installation operations. Packaging waste is considered in installation.
Use	The product does not require special maintenance operations.
End of life	End of life optimized to decrease the amount of waste and allow recovery of the product components and materials This product contains Brominate FR(260g) that should be separated from the stream of waste so as to optimize end-of-life treatment. The location of these components and other recommendations are given in the End of Life Instruction document which is available on the Schneider-Electric Green Premium website http://www2.schneider-electric.com/sites/corporate/en/products-services/green-premium/green-premium.page Recyclability potential: 54% Based on "ECO'DEEE recyclability and recoverability calculation method" (version V1, 20 Sep. 2008 presented to the French Agency for Environment and Energy Management: ADEME).



Environmental impacts

Reference life time	30 years			
Installation elements	No special components needed			
Use scenario	use rate:70% of the RLT, there is no need to consider loading rate accoridng PSR0001.			
Geographical representativeness	Europe			
Technological representativeness	It's a cable reel for enwinding cables and energy transmission.			
Energy model used	Manufacturing	Installation	Use	End of life
	Energy model used: China	Electricity grid mix; AC; consumption mix, at consumer; 230V; FR	Electricity grid mix; AC; consumption mix, at consumer; 230V; FR	Electricity grid mix; AC; consumption mix, at consumer; 230V; FR

Compulsory indicators		CRL 20M HO5VVF 3G1.5 IP20 CONTOUR - IMT33142					
Impact indicators	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Contribution to mineral resources depletion	kg Sb eq	2.63E-03	6.33E-04	0*	0*	1.99E-03	0*
Contribution to the soil and water acidification	kg SO ₂ eq	1.53E+01	8.69E-02	3.02E-03	0*	1.52E+01	0*
Contribution to water eutrophication	kg PO ₄ ³⁻ eq	1.40E+00	1.49E-02	6.96E-04	0*	1.39E+00	3.79E-04
Contribution to global warming	kg CO ₂ eq	4.12E+03	2.78E+01	6.62E-01	0*	4.09E+03	7.29E-01
Contribution to ozone layer depletion	kg CFC11 eq	5.84E-03	2.98E-06	0*	0*	5.84E-03	0*
Contribution to photochemical oxidation	kg C ₂ H ₄ eq	8.88E-01	8.22E-03	2.16E-04	0*	8.80E-01	1.40E-04
Resources use	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Net use of freshwater	m3	9.68E+04	0*	0*	0*	9.68E+04	0*
Total Primary Energy	MJ	3.73E+05	5.69E+02	0*	0*	3.73E+05	0*



Optional indicators		CRL 20M HO5VVF 3G1.5 IP20 CONTOUR - IMT33142					
Impact indicators	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Contribution to fossil resources depletion	MJ	4.74E+04	4.01E+02	9.30E+00	0*	4.70E+04	5.95E+00
Contribution to air pollution	m³	1.40E+05	3.36E+03	2.82E+01	0*	1.36E+05	4.72E+01
Contribution to water pollution	m³	2.12E+05	4.65E+03	1.09E+02	0*	2.07E+05	5.73E+01
Resources use	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Use of secondary material	kg	1.40E+00	1.40E+00	0*	0*	0*	0*
Total use of renewable primary energy resources	MJ	2.71E+04	3.05E+01	0*	0*	2.70E+04	0*
Total use of non-renewable primary energy resources	MJ	3.46E+05	5.38E+02	0*	0*	3.46E+05	0*
Use of renewable primary energy excluding renewable primary energy used as raw material	MJ	2.71E+04	2.75E+01	0*	0*	2.70E+04	0*
Use of renewable primary energy resources used as raw material	MJ	2.95E+00	2.95E+00	0*	0*	0*	0*
Use of non renewable primary energy excluding non renewable primary energy used as raw material	MJ	3.46E+05	4.68E+02	0*	0*	3.46E+05	0*
Use of non renewable primary energy resources used as raw material	MJ	6.99E+01	6.99E+01	0*	0*	0*	0*
Use of non renewable secondary fuels	MJ	0.00E+00	0*	0*	0*	0*	0*
Use of renewable secondary fuels	MJ	0.00E+00	0*	0*	0*	0*	0*
Waste categories	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Hazardous waste disposed	kg	1.84E+01	4.19E+00	0*	3.56E-03	7.71E+00	6.53E+00
Non hazardous waste disposed	kg	8.37E+03	5.39E+00	0*	0*	8.36E+03	0*
Radioactive waste disposed	kg	1.23E+02	0*	0*	0*	1.23E+02	0*
Other environmental information	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Materials for recycling	kg	3.54E+00	4.50E-01	0*	7.08E-01	0*	2.38E+00
Components for reuse	kg	0.00E+00	0*	0*	0*	0*	0*
Materials for energy recovery	kg	1.04E-01	1.11E-03	0*	0*	0*	1.03E-01
Exported Energy	MJ	0.00E+00	0*	0*	0*	0*	0*

* represents less than 0.01% of the total life cycle of the reference flow

Life cycle assessment performed with EIME version EIME v5.7.0.2, database version 2016-11 in compliance with ISO14044.

The use phase is the life cycle phase which has the greatest impact on the majority of environmental indicators (based on compulsory indicators).

Please note that the values given above are only valid within the context specified and cannot be used directly to draw up the environmental assessment of an installation.

<i>Registration number</i>	ENVPEP1802003_V1	<i>Drafting rules</i>	PCR-ed3-EN-2015 04 02
<i>Date of issue</i>	02/2018	<i>Supplemented by</i>	PSR-0001-ed3-EN-2015 10 16
<i>Validity period</i>	5 years	<i>Information and reference documents</i>	www.pep-ecopassport.org
<i>Independent verification of the declaration and data</i>			
Internal	X	External	
<i>The elements of the present PEP cannot be compared with elements from another program.</i>			
<i>Document in compliance with ISO 14021:2016 « Environmental labels and declarations - Self-declared environmental claims (Type II environmental labelling) »</i>			

Schneider Electric Industries SAS

Country Customer Care Center

<http://www.schneider-electric.com/contact>

35, rue Joseph Monier

CS 30323

F- 92506 Rueil Malmaison Cedex

RCS Nanterre 954 503 439

Capital social 896 313 776 €

www.schneider-electric.com

Published by Schneider Electric

ENVPEP1802003_V1

© 2017 - Schneider Electric – All rights reserved

02/2018