



Quick guide til hurtigt valg

Terra AC-ladeboks

Ikke MID certificerede ladere:

Type	TAC-W4-S-0	TAC-W7-G5-R-0	TAC-W11-G5-R-0	TAC-W22-G5-R-C-0	TAC-W22-T-0	TAC-W22-T-R-0
Forsyningsspænding	110-230 V AC	110-230 V AC	380-415 V AC	380-415 V AC	380-415 V AC	380-415 V AC
Maksimal ladeeffekt	3,7 kW / 16 A	7,4 kW / 32 A	11 kW / 16 A	22 kW / 32 A	22 kW / 32 A	22 kW / 32 A
Fast 5 m kabel med Type 2 stik	-	✓	✓	✓	-	-
RFID	-	✓	✓	✓	-	✓
Indbygget DC lækstrøms detektering	✓	✓	✓	✓	✓	✓
4G modem	-	-	-	✓	-	-
WiFi, Ethernet og Bluetooth	✓	✓	✓	✓	✓	✓
EAN	8719874451284	8719874450935	8719874450942	8719874450959	8719874450898	8719874450904

MID certificerede ladere:

Type	TAC-W7-T-RD-MC-0	TAC-W22-G5-RD-MC-0	TAC-W22-T-RD-M-0	TAC-W22-T-RD-MC-0
Forsyningsspænding	110-230 V AC	380-415 V AC	380-415 V AC	380-415 V AC
Maksimal ladeeffekt	7,4 kW / 32 A	22 kW / 32 A	22 kW / 32 A	22 kW / 32 A
Fast 5 m kabel med Type 2 stik	-	✓	-	-
RFID	✓	✓	✓	✓
Indbygget DC lækstrøms detektering	✓	✓	✓	✓
4G modem	✓	✓	-	✓
WiFi, Ethernet og Bluetooth	✓	✓	✓	✓
EAN	8719874450966	8719874451000	8719874450973	8719874450980

Pedestaler:

Type	TAC-P1-2 rectangular	TAC pedestal single	TAC pedestal double
Beskrivelse	Aluminiums pedestal med mulighed for DIN skinne materiel i standen	Aluminiums pedestal	Aluminiums pedestal
Antal ladere	1 el. 2 stk. Ryg mod ryg	1 stk.	2 stk. Ryg mod ryg
DIN skinne plads	24 moduler	-	-
Tæthedsklasse	IP 54	-	-
Stødfasthed	IK10	IK10	IK10
Dimension (mm)	120x210x1410	100x200x1403	100x200x1403
EAN	8719874451178	8719874451635	8719874451949

Tilbehør:

Type	SER-abbRFIDtags
Beskrivelse	5 stk. RFID kort med ABB logo
EAN	8719874451185



Læs mere: solutions.abb/terraacwallbox

Copyright© 2020 ABB - Alle rettigheder forbeholdes.