

the norm plug

norm

STANDARD

SIDE OUTLET REWIRABLE SCHUKO PLUG WITH EARTH CONTACT.
FOR INDOOR USE WITH ELECTRICAL DEVICES AND COMPONENTS
COMPLIANT WITH SCHUKO STANDARDS.

APPLIED STANDARDS:
UNE 20315 -1-1, UNE 20315-1-2 (IEC 60884-1 + CEE 7)

DIMENSIONS

	HEIGHT(A)	WIDTH(B)	DEPTH(C)	FROM SOCKET(D)
EXTERNAL	43 MM	40 MM	48 MM	11 MM

INSTALLATION

	WIRING	SCREWDRIVER
RECOMENDED	Ø9 MM (3 X 1,5 MM²)	PH1 PLANO/FLAT (0,8MM MAX)

CONFIGURATION	POLES	EARTHING SYSTEM	OUTLET	TYPE	TERMINAL
	2 P+T	LATERAL / SIDE	LATERAL / SIDE	C2B (CEE7/IV)	SCREW TYPE

TECHNICAL DATA	RATED VOLTAGE	RATED CURRENT	RATED POWER	FREQUENCY	INSULATION RESISTANCE	DIELECTRIC STRENGTH
	250 V	16 >	3680 W	50 HZ	5MΩ@500VDC	2 KV

COLOUR COLLECTION

	MATT SURFACE	SHINY SURFACE
PRODUCT NAME	 NORM 43021 / WHITE / MATT	 NORM 43011 / WHITE / SHINY
COLOR SURFACE	 NORM 43022 / BLACK / MATT	 NORM 43012 / BLACK / SHINY
	 NORM 43023 / GREY / MATT	
	 NORM 43024 / GREEN / MATT	
	 NORM 43027 / BLUE / MATT	
	 NORM 43025 / ORANGE / MATT	
	 NORM 43026 / RED / MATT	

PACKAGING BOX	HEIGHT	WIDTH	LENGTH	WEIGHT INCL. PLUG
CARDBOARD	70 MM	70 MM	70 MM	0,48 KG

CERTIFICATIONS

KEMA-KEUR INTERTEK CE



BY NORM APS
COPENHAGEN, DENMARK
VAT 43029428

FOR MORE INFORMATION:
NORMPLUG.COM

PERSONAL CONTACT:
KASPER KASTOFT NIELSEN, PARTNER
+45 26131879
KASPER@NORMPLUG.COM