



Illustrative picture

SPECIFICS

Description	Product type	3 ways movable multiplier IP44
	Article code	1417
	Commercial Series	SERIES 13 IEC 309 IP44

General Data

Poles	N° 3P+N+E	Type of material	Abs / Nylon							
Current	A 32	Terminal inlet diameter	mm 11,5 - 20							
Voltage	V~ 200/346-240/415	Dimensional stability	°C -25 /+70							
Earth contact position	h 6	Resistance glow wire test	°C +650 / +850							
Degree of protection	IP 44	Working temperature	°C , -25 + 55							
Impact Resistance	IK 8	Weight	kg 1							
Insulation Resistance	MΩ >10									
Dimensions LxDxH	cm 225X220X75									
Behaviour with chemical and atmospheric agents										
Saline Solution	Acids		Bases		Solvents				Mineral Oil	UV rays
	Concentrated	Diluted	Concentrated	Diluted	Hexane	Benzol	Acetone	Alcohol		
Resistant	Limited Resistant	Resistant	Resistant	Resistant	Limited Resistant	Limited Resistant	Resistant	Resistant	Resistant	Resistant

Standards	CEI EN 60309-1	CEI EN 60309-2	2014/35/UE
-----------	----------------	----------------	------------

Features package	Descriptions		N/pieces	Weight/kg
	Article		1	1
	Package innerbox		3	3,09
	Packaging			

Dimensions

Technical drawing of a 4-pole circuit breaker. Dimension A is the total width of the device. Dimension B is the height of the main body. Dimension C is the height of the handle assembly.

Amp	16A			32A		
Poles:	3	4	5	3	4	5
A	229	230	266	287	287	287
B	220	224	256	277	277	281
C	46.5	53.5	60.5	62.5	62.5	69.5



Reg. A.E.E n° IT17100000010057



Rev	Date	Technical Manager
01	7/1/20	Romano Rosi

CERTIFICATO N° 9105.ROS3 - UNI EN ISO 9001:2015