



Illustrative picture

SPECIFICS

Description	Product type	3 ways movable multiplier with 2 mt flexible cable 50/60 Hz IP44
	Article code	1515
	Commercial Series	SERIES 13 IEC 309 IP44

General Data

Poles	N°	3P+N+E	Type of material	ABS						
Current	A	16	Dimensional stability	°C -25 /+70						
Voltage	V~	200/346-240/415	Resistance glow wire test	°C +650 / +850						
Earth contact position	h	6								
Degree of protection	IP	44								
Impact Resistance	IK	8								
Insulation Resistance	MΩ	>10								
Dimensions LxDxH	cm	225X220X75								
Behaviour with chemical and atmospheric agents										
Saline Solution	Acids		Bases		Solvents				Mineral Oil	UV rays
	Concentrated	Diluted	Concentrated	Diluted	Hexane	Benzol	Acetone	Alcohol		
Resistant 	Limited Resistant 	Resistant 	Resistant 	Resistant 	Limited Resistant 	Limited Resistant 	Resistant 	Resistant 	Resistant 	Resistant 

Standards	
-----------	--

Features package	Descriptions		N/pieces	Weight/kg
	Article		1	/
	Package innerbox		1	/
	Packaging			

Dimensions

Technical drawing of a 3-phase 4-wire circuit breaker. The drawing shows the front view of the device with its three main switching poles and a central neutral pole. Dimension A is indicated as the total width of the device, and dimension B is indicated as the total height. The device is shown in a slightly open position, revealing the internal mechanism.

Amp	16A			32A		
Poles	3	4	5	3	4	5
A	283	284	336	342	342	342
B	220	224	256	277	277	281



CERTIFICATO N° 9105.ROS3 - UNI EN ISO 9001:2015

Reg. A.E.E n° IT17100000010057

DATA	RESPONSABILE TECNICO
30/04/2021	Romano Rosi