



Illustrative picture

SPECIFICS

Description	Product type	3 ways movable multiplier with 2 mt flexible cable 50/60 Hz IP44
	Article code	1517
	Commercial Series	SERIES 13 IEC 309 IP44

General Data	Poles	N° 3P+N+E	Type of material	ABS						
	Current	A 32	Dimensional stability	°C -25 /+70						
	Voltage	V~ 200/346-240/415	Resistance glow wire test	°C +650 / +850						
	Earth contact position	h 6								
	Degree of protection	IP 44								
	Impact Resistance	IK 8								
	Insulation Resistance	MΩ >10								
	Dimensions LxDxH	cm 225X220X75								
	Behaviour with chemical and atmospheric agents									
Saline Solution	Acids		Bases		Solvents				Mineral Oil	UV rays
	Concentrated	Diluted	Concentrated	Diluted	Hexane	Benzol	Acetone	Alcohol		
Resistant	Limited Resistant	Resistant	Resistant	Resistant	Limited Resistant	Limited Resistant	Resistant	Resistant	Resistant	Resistant

Standards	
-----------	--

Features package	Descriptions		N/pieces	Weight/kg
	Article		1	/
	Package innerbox		1	/
	Packaging			

Dimensions

Technical drawing of a 3-pole circuit breaker. Dimension A is the total width of the device, and dimension B is the height of the main body.

Amp	16A			32A		
Poles	3	4	5	3	4	5
A	283	284	336	342	342	342
B	220	224	256	277	277	281



Reg. A.E.E n° IT17100000010057

CERTIFICATO N° 9105.ROS3 - UNI EN ISO 9001:2015

DATA	RESPONSABILE TECNICO
30/04/2021	Romano Rosi