

Clamp thermometer operated with smartphone

testo 115i

Compact professional measuring instrument from the Testo Smart Probes series for use with smartphones/tablets

Measurement of flow and return temperature of heating systems

Temperature measurement on refrigeration systems for calculation of superheating and subcooling

Fast identification of temperature changes by graphic progression display

Measurement data analyzed and sent via testo Smart App

Problem-free use at measuring points that are a long distance apart – Bluetooth® range up to 100 m



In conjunction with a smartphone or tablet, the handy testo 115i clamp thermometer is suitable for servicing and troubleshooting on air conditioning and refrigeration systems, as well as for their installation. In addition, the measuring instrument can also be used to measure flow and return temperatures. The testo 115i makes it considerably easier to work on measuring points that are a long distance apart, thanks to wireless connection to a smartphone or tablet.

And simultaneous use of the testo 549i high-pressure measuring instrument also enables calculation of individual refrigeration system parameters, such as superheating and subcooling. Users can read off their measuring values conveniently via the testo Smart App installed on the terminal device. All measurement data are presented either as a graph or a table. Finally, the measurement data reports can be sent directly as pdf or Excel files.

Technical data/accessories

testo 115i


testo 115i, clamp thermometer operated with smartphone, for measurement on pipelines with diameters of 6 to max. 35 mm, including batteries and calibration protocol

Order no. 0560 2115 02



testo Smart App

The App turns your smartphone/tablet into the display for the testo 115i. Both the operation of the measuring instrument and the display of the readings are achieved by Bluetooth® via the testo Smart App on your smartphone or tablet – irrespective of the measuring location. In addition, you can use the App to create measurement reports, add photos and comments to these and send them by e-mail. For iOS and Android.



Sensor type

NTC

Measuring range	-40 to +150 °C
Accuracy ±1 digit	±1.3 °C (-20 to +85 °C)
Resolution	0.1 °C

General technical data

Compatibility	requires iOS 11.0 or newer / Android 6.0 or newer requires mobile terminal device with Bluetooth® 4.0
Storage temperature	-20 to +60 °C
Operating temperature	-20 to +50 °C
Battery type	3 micro batteries AAA
Battery life	150 hrs
Dimensions	183 x 90 x 30 mm
Bluetooth® range	up to 100 m
A3 and A2L compatible	✓

Accessories

Order no.

testo Smart Case (refrigeration) for the storage and transport of 2 x testo 115i and 2 x testo 549i, dimensions 250 x 180 x 70 mm	0516 0240	
testo Smart Case (heating) for the storage and transport of testo 115i, testo 410i, testo 510i, testo 549i and testo 805i, dimensions 250 x 180 x 70 mm	0516 0270	
ISO temperature calibration certificate, one-point calibration for clamp thermometer, calibration point +60 °C	0520 0072	



Hassellunden 11A, 2765 Smørum
Tel. 45 95 04 10
info@buhl-bonsoe.dk
www.buhl-bonsoe.dk