

ActiV?Non-Diode Base

Part No. **C4408**



Overview

Compatible with C-TEC's entire range of ActiV fire detectors.

Ideal for use in some non-UK territories where head-out monitoring is not required.

Third-party certified to the relevant parts of EN54 in conjunction with our ActiV detectors.

Easy to fit with lots of working space.

Can be ceiling mounted in any orientation due to the true 360° degree viewing angle of the LED indicator strips on all ActiV detectors.

Integrated detector/base locking mechanism, head removal tool and ID tag.

Simple 'click and twist' design.

Remote LED terminals for the optional connection to a BF318 Remote indicator.

C4408D diode and C4408R relay bases also available.

Technical Specifications

Approvals/certifications	Certified to the relevant parts of EN54 by Intertek as part of our ActiV fire detector certifications.
Supply wiring	2-wire monitored, polarity sensitive.
Connections	(1) +V In; (2) +V Out; (3) Remote LED +V; (4) 0V; (5) 0V; (6) Screen; (7) Screen. Terminals can accept up to 2.5mm fire rated cable.
Product dimensions (mm)	102.2mm diameter x 20.5mm deep.
Construction & finish	White polycarbonate rated to UL94 V-2 with bright tin plated steel terminals fitted with nickel plated steel screws/washers.
IP Rating	IP42.
Weight	55g.
Notes	THIS DEVICE DOES NOT INCLUDE A SCHOTTKY DIODE AND MUST NOT BE USED ON SYSTEMS REQUIRING HEAD OUT MONITORING.