






NEOFLEX® PVC are highly flexible triple layer PVC hoses with integrated crosslinked and longitudinal reinforcement.
 Certified in Denmark, Norway and Sweden for use in technical water supply systems to max 25°C (See technical specifications for details).

**Technical specifications :**

Technical specifications:			
Article no.	S212	S420	S422
Nominal size	DN6	DN10	
Inside diameter hose	Ø7,5	Ø10,0	
Outside diameter hose, without braiding	Ø12,3	Ø16,4	
Colour	White	Grey	Grey
Surface	Smooth	Smooth	Ribbed
Braiding – bandwire	-	-	-
PVC coating	-	-	-
Max. work pressure	10 bar		
Max. temperature	25°C		
Min. flow at 3 bar	21 l/min	45 l/min	
Approvals	VA (DK) – SINTEF (N) - RISE (S)		

Standard fittings :

												
	Female elbow			Female			Male			Female nylon	Elbow nylon	
	3/8"	1/2"	3/4"	3/8"	1/2"	3/4"	1/4"	3/8"	1/2"	3/4"	3/4"	3/4"
DN6				x	x	x		x	x			
DN10	x	x	x	x	x	x	x	x	x	x	x	x

(Other fittings on request)

Applications* :

Dish washer



Washing machine



Toilet

*For other purposes, please contact Neoperl Nordic A/S