

Specifikationer



Billedet er repræsentativt



Eaton 9SX3000I

Eaton 9SX UPS, 3000 VA, 2700 W, Input: C20, Outputs: (8) C13, (1) C19, Tower

General specifications

PRODUCT NAME	Eaton 9SX UPS
CATALOG NUMBER	9SX3000I
UPC	743172090997
PRODUCT LENGTH/DEPTH	412 mm
PRODUCT HEIGHT	346 mm
PRODUCT WIDTH	214 mm
PRODUCT WEIGHT	33.4 kg
COMPLIANCES	CE Marked TUV cULus Listed CSA 22.2 FCC part 15 Class B CISPR22 Class B
CERTIFICATIONS	IEC/EN 62040-1 UL 1778 IEC/EN 62040-2 CE cULus Listed EAC



Powering Business Worldwide

Additional information

AUTO SHUTDOWN FUNCTION	Yes
COLOR	Black
CONSTRUCTION TYPE	Free standing model
EFFICIENCY AT MAX. LOAD	92.4
HOT SWAP POWER	No
INTERNAL BYPASS	Yes

PACKAGE CONTENTS	• UPS • Input cable • (2) IEC-IEC output cables • USB cable • Serial cable • Safety instructions • Quickstart guide
-------------------------	---

PHASE (INPUT)	1
PHASE (OUTPUT)	1
RACK MOUNTING KIT	No

Battery specifications

BATTERY MANAGEMENT

- ABM & Temperature compensated charging method (user selectable)
- Automatic battery test
- Deep discharge protection
- Automatic recognition of external battery units

BATTERY QUANTITY	8
BATTERY RATING	12 V / 9 Ah
BATTERY REPLACEMENT	Hot-swappable internal batteries and extended battery modules (EBMs)
BATTERY TYPE	Sealed, lead-acid
EXTENDED BATTERY CAPABILITY	Yes
RUNTIME GRAPH	View runtime graph

Communication

COMMUNICATION

- USB port (HID compliant)
- Serial port (RS232)
- Mini-terminal block for remote power off
- Mini-terminal block for output relay
- Dry contacts (2 outputs, 1 input, optocoupler, DB9)

ETHERNET INTERFACE

No

EXPANSION SLOTS

One slot for optional communication card

INCLUDES NETWORK CARD

No

POTENTIAL FREE SWITCH CONTACT

Yes

SOFTWARE COMPATIBILITY

Eaton Intelligent Power Manager, Eaton Intelligent Power Protector

TYPE OF INTERFACE

Other

USER INTERFACE

Multilingual graphical LCD display

Electrical output

FEED TYPE

1

OUTPUT NOMINAL VOLTAGE

230V default
(200/208/220/230/240V)

OUTPUT POWER FACTOR

0.9

OUTPUT VOLTAGE RANGE

200/208/220/230/240 V +/- 2%

OUTPUT WAVEFORM

Sine wave

RECEPTACLE

(8) C13, (1) C19

TOPOLOGY

Online/Double-conversion

VA RATING

3000 VA

VOLTAGE

230V

VOLTAGE DISTORTION OUTPUT (LINEAR LOAD) - MAX

3

WATTAGE

2700 W

Electrical input

INPUT CONNECTION

C20

INPUT CORD LENGTH

1.8m

INPUT FREQUENCY RANGE

40-70 Hz

INPUT NOMINAL VOLTAGE

230V default
(200/208/220/230/240/250V)

INPUT POWER FACTOR

>.99

INPUT VOLTAGE RANGE

200-276 Vac without derating (up to 140-276 Vac with derating)

NOMINAL FREQUENCY

50/60 Hz

Environmental

ALTITUDE

3000 m

NOISE LEVEL

<45 dB at 1 meter

RELATIVE HUMIDITY

0-96% non-condensing

TEMPERATURE RANGE

0° to 40°C (32° to 104°F)

Ressourcer

COMPLIANCE
INFORMATION

[EU declaration of
conformity Eaton 9SX UPS](#)

PROJEKTNAMN:

PROJEKTNUMMER:

KLARGJORT AF:

DATO:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Irland
Eaton.com

© 2026 Eaton. Alle rettigheder forbeholdt.

Følg os på de sociale medier for at få
de seneste produkt- og
supportnyheder.

