

Safety transformer, 24VA Primary 230 V AC, 50Hz, secondary 8 V, 12 V AC With PTC fuse, 3MW++



Model	
Product brand name	SENTRON
Product designation	Safety transformer
Design of the transformer	Safety transformer
General technical data	
Supplied active power / maximum	24 W
Voltage	
Input voltage	230 V
Output voltage	
• _1 / rated value	8 V
• _2 / rated value	12 V
Dissipation	
Power loss [W] / for rated value of the current / at AC / in hot operating state / per pole	8 W
Electricity	
Output current	
• maximum	2 A

- _1 / rated value
- _2 / rated value

2 A
2 A

Suitability

Suitability for integration

- surface-mounted installation
- flush mounting

No
No

Product details

Product component / switch

No

Product function

Product function / Thermal protection

Yes

Inputs Outputs

Property of the output / Short-circuit proof

Yes

Mechanical Design

Height

64 mm

Width

54 mm

Length

90 mm

Number of width units

3

Mounting type / Side-by-side mounting

Yes

**General Product
Approval**

**Declaration of
Conformity**

other



[Confirmation](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=4AC3724-0>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/4AC3724-0>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=4AC3724-0

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>

