



SPCK420/SPCK421

Standard Keypad

LCD keypad with 2 x 16 character display/card reader

- **Standard keypad with 2 x 16 character LCD display**
- **Integrated card reader**
- **Wireless plugging option**

User friendly operation: The standard keypad with its 2 line LCD display, soft keys, and multi-dimensional navigation key is ideal to operate smaller systems or single areas in a user friendly way.

Authorized access: The integrated card reader enables quick setting and unsetting of areas by use of a proximity card only or in combination with a valid user PIN.

Wireless Access Point: The optional wireless module adds a wireless access point for wireless detectors and remote controls to allow excellent reception quality in the keypad area.

Technical data

SPCK420/SPCK421

Functional Data	
Display	2 x 16 characters
LED indicators	3 status LEDs
Special keys	2 soft keys, 1 multi-dimensional navigation key
Radio module	Optional (SPCW112)
Interfaces	X-BUS (in, out)
Power Data	
Operating voltage	9.5 ~ 14 V DC
Mechanical Data	
Tamper contact	Front/back spring tamper
Operating temperature	5° ~ +40 °C
Housing	Plastic Housing (Polycarbonate)
Colour	RAL 9003 (signal white)
Dimensions	112 x 185 x 28 mm
Weight	0.380 kg

SPCK420

Power Data	
Operating current	Max. 90 mA at 12 V DC (backlight, LEDs, sounder operated)
Quiescent current	Max. 45 mA at 12 V DC

SPCK421

Functional Data	
Card Reader	Integrated (125kHz, EM 4102)
Power Data	
Operating current	Max. 110 mA at 12 V DC (backlight, LEDs, sounder, reader operated)
Quiescent current	Max. 80 mA at 12 V DC

Ordering data

S54543-F101-A100
S54543-F102-A100

SPCK420.100 Standard Keypad
SPCK421.100 Standard Keypad w. Card Reader